



PRODUCT INFORMATION



Stellar Solutions, Inc.
4511 Prime Parkway
McHenry, IL 60050
Phone (847) 854-2800
Fax (847) 854-2830
stellar@citrisurf.com
www.citrisurf.com

Technical Data:

Description: *CitriSurf 77* is a high quality blend of chemicals formulated for the cleaning and passivation of stainless steel products. It is provided in trigger sprayer bottles for applications where it is desired to spray the product on a local area. *CitriSurf 77* is specifically designed to provide a portable, low cost and efficient removal of contaminants and all free iron from the surface of stainless steel, providing the highest chrome oxide levels possible.

Physical Properties:

Specific Gravity	1.04
Approx. wt. /gallon	8.7 lb/gal
Viscosity	2 cps
Form	Liquid
Chemical Composition	Citric acid, water, proprietary ingredients
Operating Temperature	Room temp or higher
Flash Point	None
Water solubility	Complete
Normal working concentration	Full strength
pH at working concentration	1.6

Packaging: 22 oz. trigger sprayer bottles.

Application Procedure: *CitriSurf* is an excellent cleaner by itself for many cleaning and passivation processes. However, to assure best results the parts or areas to be passivated may be cleaned with an appropriate cleaning solution prior to treatment with *CitriSurf* solution, especially when heavy grease and oils are present. If there is rust on the surface that must be removed, you may want to use *CitriSurf 77 Plus* which has additional additives to aid in rust removal.

The parts or areas to be cleaned and passivated should be sprayed, immersed or wiped with *CitriSurf 77* to completely wet the surfaces, especially in crevices or in areas where any rust or corrosion may have occurred. The surface must be soaked or left moist with the *CitriSurf 77* solution for a period of 15-30 minutes at room temperature. After soaking, rinse the surface with clean water. The surface can then be wiped dry with a clean cloth or appropriate absorbent medium. Allow the surface to air dry prior to use. *CitriSurf 77* will not harm most metal appliances or surfaces, and will enhance the brightness when used as directed.

Notes on Use: Although very safe in normal use, *CitriSurf 77* is a citric acid based material, and as such it may cause irritation to exposed surfaces of the body. **See Material Safety Data Sheet before using this material.** Rubber or plastic gloves should be worn to apply the product to the surface or to wipe it dry.

Do not apply *CitriSurf 77* to electrical wiring or other conductive material that is connected to electrical current without first turning off all electricity! *CitriSurf* is a water based conductive material. Serious injury or death can occur from electrical shock.

Do not leave concrete or carbon steel exposed to *CitriSurf* for any period of time. Damage to these materials will occur with prolonged exposure.

Disposal: Dispose of according to all federal, state and local regulations.

Storage: *CitriSurf 77* should be stored at temperatures between 50°F and 120°F in the bottles supplied with the product. (If accidentally frozen, thawing will return product to normal.)

Technical Services: For technical assistance, please contact Stellar Solutions at (847) 854-2800.

Specifications: *CitriSurf 77* meets all of the requirements of ASTM A-967 and AMS 2700 specifications.

Testing of your products with *CitriSurf* before using in production is recommended. Every product and facility is different, and requires testing to ensure that *CitriSurf* is compatible with the particular situation. No warranty is implied, or may be given in writing or verbally without the written permission of Stellar Solutions, Inc.

11/09



Nonfood Compounds
Program Listed A3
137375