



PRODUCT INFORMATION

Rust+Rescue™ 200

Stellar Solutions, Inc.
4511 Prime Parkway
McHenry, IL 60050
Phone (847) 854-2800
Fax (847) 854-2830
stellar@citrisurf.com
www.citrisurf.com

Technical Data:

Description: *Rust Rescue 200* is a high quality blend of chemicals formulated for the protection of stainless steel and other metal surfaces from moisture and harsh atmospheric chemicals that could lead to corrosion.

Physical Properties:

Chemical Composition	Calcium sulfonate, proprietary ingredients
Operating Temperature	70-90°F
Flash Point	150°F
Normal working concentration	Use as received

Packaging: 1 gallon or 55 gallon metal containers.

Application Procedure: To assure best results, the parts to be treated should be thoroughly cleaned to remove dirt, oils, and grease with an appropriate cleaning solution prior to treatment with *Rust Rescue 200*. If thorough cleaning is not possible during use in the field, wipe the surface free of dirt and oils prior to application. All equipment, mixers, applicators or pumps should be clean and dry prior to use.

Prior to use, mix thoroughly by shaking or stirring. Apply a light coat of *Rust Rescue 200* to the surface to be protected with a clean soft cloth, sprayer, brush or roller. Coverage is approximately 300 square feet per gallon. Wait approximately 10 minutes and then wipe off the excess product. Allow the surface to dry completely in air. Drying can be accelerated by use of a hot air oven or other drying medium such as an air blower (hair dryer).

If rust is on the surface, remove all rust first with a rust remover such as *CitriSurf 77 Plus* or *CitriSurf 2310*, using the procedure recommended for that product. Then allow surface to dry completely before applying *Rust Rescue*.

Notes on Use: Although very safe in normal use, *Rust Rescue 200* is a Calcium Sulfonate based material, and as such it may cause irritation to exposed surfaces of the body for some persons. **See Material Safety Data Sheet before using this material.** Rubber or plastic gloves should be worn to apply the product to the surface or to wipe it dry.

Disposal: Dispose of according to all federal, state and local regulations.

page 2...

Storage: *Rust Rescue 200* should be stored at temperatures between 50°F and 120°F in steel or approved plastic containers (polyethylene or polypropylene).

Technical Services: For technical assistance, please contact Stellar Solutions at (847) 854-2800.

Testing of your products with *Rust Rescue* before using in production is recommended. Every product and production facility is different, and requires testing to ensure that *Rust Rescue* is compatible with the particular situation. No warranty is implied, or may be given in writing or verbally without the written permission of Stellar Solutions, Inc.

12/10